

Product data sheet

Characteristics

LA6DK10U

auxiliary latch block TeSys D - 256...277 V DC/
AC 50...60 Hz



Local distributor code: 398254759
EAN Code: 3389110745825



Main

Range	TeSys
Product or component type	Mechanical latch block
Product compatibility	LC1D40 3 phases + neutral AC LP1D40 3 phases + neutral DC LP1D65 3 phases + neutral DC LC1D65 3 phases + neutral AC
[Uc] control circuit voltage	256/277 V AC 50/60 Hz 256/277 V DC

Complementary

Mounting location	Front side
Tripping control	Manual Electrical
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1
Power required in VA	25 for AC circuit
Power required in W	30 W for DC circuit
Mechanical durability	500000 cycles
Maximum operating rate	1200 cyc/h
On-load factor	10 %
Net weight	0.07 kg

Environment

Product certifications	UL[RETURN]CSA
IP degree of protection	IP2X conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.3 cm
Package 1 Width	5.0 cm
Package 1 Length	6.5 cm
Package 1 Weight	96.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------