

Product data sheet Characteristics

LE4K095B7

TeSys LE - enclosed DOL starter - 9 A - 24 V AC coil

EAN Code: 3389110760675



Main		
Range	TeSys	
Product name	TeSys LE	
Device short name	LE4K	
Product or component type	Enclosed DOL starter	
Device application	Standard	
Material	Polycarbonate	
Utilisation category	AC-3	
Device composition	Thermal overload relay ordered separately Contactor Fuse disconnector	
Motor power kW	4 KW at 380/400 V AC 50/60 Hz 4 KW at 415 V AC 50/60 Hz 4 KW at 440 V AC 50/60 Hz 2.2 kW at 220/230 V AC 50/60 Hz	
[Uc] control circuit voltage	24 V AC 50/60 Hz	
[Ith] Conventional free air thermal current	9 A	
Associated fuse rating	12 A 10 x 38 mm aM	
Control type	Push-button start green I Push-button stop/reset red O	

Complementary

Cable entry number	4 ISO20 top	
	4 2 Pg 13 + 2 Pg 16 top	
	4 ISO20 bottom	
	4 2 Pg 13 + 2 Pg 16 bottom	
Width	175 mm	
Height	165 mm	
Depth	146 mm	
Net weight	1.45 kg	

Environment

IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK09 conforming to IEC 60529	
Standards	IEC 60947-4-1	
Ambient air temperature for operation	-540 °C	
Environmental characteristic	Standard environment	

Contractual warranty

	,	
Warranty		18 months