

Product data sheet

Characteristics

TCSAMT31FP

tap-off box - 3 RFID station to Modbus or UNI-TELWAY - M12

Important message: We have updated the process for ordering Telemecanique Sensors products. For more information, please contact your Telemecanique Sensors representative in the UK&I at: UK.salesorders@tesensors.com. You can find all product information on the Telemecanique Sensors website: www.tesensors.com/uk/en
EAN Code: 3389119021333



Main

Range of product	Telemecanique Radio frequency identification XG
Product or component type	Connection tap-off box
Device short name	TCS
Number of channels	3
Communication port protocol	Modbus Uni-Telway
Associated smart antenna	XGCS49 XGCS89
Electrical connection	1 female connector M12 5 pins for network output (A coding) 1 male connector M12 4 pins for power supply (A coding) 1 male connector M12 5 pins (A coding) 3 female connectors M12 5 pins for stations XGCS (A coding)
[Us] rated supply voltage	24 V DC conforming to Protective Extra Low Voltage

Complementary

Supply voltage limits	19.2...29 V DC
Status LED	Supply on: 1 LED (green)
Marking	CE
Net weight	1.06 kg

Environment



Product certifications	UL
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	30...95 %
IP degree of protection	IP65
EMC filter	Class B EMC filter conforming to EN 55022 Level 3 EMC filter conforming to IEC 61000

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	16.600 cm
Package 1 Length	23.000 cm
Package 1 Weight	830.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	8

Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.532 kg


Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------


Connection Boxes



Wiring Diagram

Modbus Connections

Socket to Smart Antenna Cabling




Pin no.	Signal
1	Drain (Modbus-SHLD)
2	+ 24 VDC
3	0 V/Modbus-GND
4	D0
5	D1

Socket to Power Supply Cabling



Pin no.	Signal
1	+ 24 VDC
2	+ 24 VDC
3	0 VDC
4	0 VDC

Socket to Another Connection Box Cabling



Pin no.	Signal
1	Drain (Modbus-SHLD)
2	-
3	0 V/Modbus-GND
4	D0
5	D1

Socket to Automation Platform Cabling



Pin no.	Signal
1	Drain (Modbus-SHLD)
2	-

Pin no.	Signal
3	0 V/Modbus-GND
4	D0
5	D1