

## Product data sheet Characteristics

## XGSZ12E4503

# Ethernet copper cable, Radio frequency identification XG, M12 D coded to RJ45, 3 m

Important message: We have updated the process for ordering Telemecanique Sensors products. For more information, please contact your Telemecanique Sensors representative in the UK&I at: UK.salesorders@tesensors.comYou can find all product information on the Telemecanique Sensors website: www.tesensors.com/uk/en

EAN Code: 3389119075626



#### Main

Range of product	Telemecanique Radio frequency identification XG	
Accessory / separate part category	Connection accessories	
Accessory / separate part type	Connecting cable	
Product or component type	Ethernet copper cable	
Product compatibility	XUW XGSZ33ETH XGSZ33EIP	
Accessory / separate part destination	Ethernet network	

Complementary

3 m	
100 Mbit/s	
2 twisted shielded pairs	
5e	
AWG 26	
1 male connector, M12 straight connector with 4 pin(s) - encoding type: D coding 1 male connector, RJ45 straight connector with 4 pin(s)	
Copper	
PUR	

#### **Environment**

IP degree of protection	IP67
Standards	EIA/TIA-568 IEC 60754-1
	ISO/IEC 11801 Ed.2, 2002

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.400 cm
Package 1 Width	18.300 cm
Package 1 Length	18.500 cm
Package 1 Weight	154.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or it hese products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

40 cm	
1.871 kg	

REACh Regulation	REACh Declaration
U RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free Yes	
RoHS exemption information	₫Yes

### Contractual warranty

Warranty	18 m	onths
vvarianty	10 111	ontrio

## Product data sheet Connections and Schema

## XGSZ12E4503

### Wiring Diagram

