

## Product data sheet Characteristics

# XAWG210EX

Control station, plastic, start stop function, 2 flush push buttons, green, red, 1 NO + 1 NC, ATEX



Main	
Range of product	Harmony XAW
Product or component type	Complete control station
Device short name	XAWG
Control station application	Start-Stop function
Material	Glass fibre reinforced
Control station composition	1 flush push-button, green, spring return 1 NO 1 flush push-button, red, spring return 1 NC

Complementary

Complementary		
Colour of base of enclosure	Black	
Colour of cover	Black	
Cable entry	1 entry for ISO M20 cable gland	
Width	85 mm	
Depth	70 mm	
Height	146 mm	
Net weight	0.705 kg	
Marking	Ex tb IIIC T85°C Db IP65	
Mechanical durability	5000000 cycles	
Short-circuit protection	10 A cartridge fuse type gG	
[le] rated operational current	3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1	

#### Environment

Ambient air temperature for operation	-2060 °C
Overvoltage category	II conforming to IEC 60536
IP degree of protection	IP65 conforming to IEC 60529
Standards	IEC 60079-0:2009
	EN 60079-31:2009
	IEC 60947-5-4
	IEC 61000-6-2
	IEC 60947-1
	IEC 60947-5-1
	IEC 60079-0:2007
	IEC 60079-31:2008
	IEC 60947-5-5
	ISO 13850
Directives	94/9/EC - ATEX directive
Dust zone	Zone 21 - 22
Product certifications	INERIS 04ATEX0023X

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

### Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	9.0 cm
Package 1 Length	23.5 cm
Package 1 Weight	705.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.138 kg

### Offer Sustainability

REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes

#### Contractual warranty

Warranty	18 months
----------	-----------