

Product data sheet Characteristics

XBTZ9740

direct connection cable - L = 2.5 m - 1 male SUB-D 9 + 1 male SUB-D25



Main	ıin		
Range of product	Harmony XBT		
Accessory / separate part category	Connection accessories		
Accessory / separate part type	Connecting cable		
Accessory / separate part designation	Direct connection cable		
Accessory / separate part destination	XBT terminal		
Cable length	2.5 m		

Complementary

XBTR411	
XBTN410	
XBTNU400	
XBTN401	
XBTR410	
Harmony HMI GTO	
Omron CQM1, CVM1, CPM1, CPM2, CJ1, CS1	
1 male connector SUB-D 25	
1 male connector SUB-D 9	
Sysmacway	
RS232	
0.21 kg	
	XBTN410 XBTNU400 XBTNU400 XBTN401 XBTR410 Harmony HMI GTO Omron CQM1, CVM1, CPM1, CPM2, CJ1, CS1 1 male connector SUB-D 25 1 male connector SUB-D 9 Sysmacway RS232

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.0 cm	
Package 1 Width	15.0 cm	
Package 1 Length	15.0 cm	
Package 1 Weight	192.0 g	

Offer Sustainability

REACh Regulation	☑REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

oontractaar warranty		
Warranty	18 months	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.