

Product data sheet Characteristics

XGHB440845

RFID electronic tag - 13.56 MHz - flat form 40 x 40 x 15 - 8192 Bytes



Main

Wilding			
Range of product	Telemecanique Radio frequency identification XG		
Product or component type	Electronic tag		
RFID electronic tag name	XGHB		
RFID frequency	13.56 MHz		
Design	Flat form 40 x 40 x 15		
Memory capacity	8 kB		
Associated smart antenna	XGCS		
[Sn] nominal sensing distance	25 Mm with XGCS49 39 Mm with XGCS89 39 mm with XGCS85		
Outer dimension	40 x 40 x 15 mm		
Quantity per set	Set of 1		
Read time	6 + 0.25 x (number of 16-bit words) ms		
Write time	6 + 0.25 x (number of 16-bit words) ms		
IP degree of protection	IP68		
Eixing mode By clips By screws			

Complementary

Read/write	
Read/write	
1000000000	
1000000000 at -2570 °C	
2.3 M/S with XGCS49 (read a serial number) 1.8 M/S with XGCS49 (read a word) 1.7 M/S with XGCS49 (read or write 10 words) 3.8 M/S with XGCS89 (read a serial number) 3 M/S with XGCS89 (read a word) 2.6 M/S with XGCS89 (read or write 10 words) 3.8 M/S with XGCS85 (read a serial number) 3 M/S with XGCS85 (read a word) 2.6 m/s with XGCS85 (read or write 10 words)	
10 year(s)	
Possible on metal support	
PBT (polybutylene terephthalate)	
0.031 kg	
	10000000000 at -2570 °C 2.3 M/S with XGCS49 (read a serial number) 1.8 M/S with XGCS49 (read a word) 1.7 M/S with XGCS49 (read or write 10 words) 3.8 M/S with XGCS89 (read a serial number) 3 M/S with XGCS89 (read a word) 2.6 M/S with XGCS89 (read or write 10 words) 3.8 M/S with XGCS85 (read a serial number) 3 M/S with XGCS85 (read a word) 2.6 m/s with XGCS85 (read or write 10 words) 10 year(s) Possible on metal support PBT (polybutylene terephthalate)

Environment

Standards	ISO 14443	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Vibration resistance	2 mm conforming to EN 60068-2-6 (f = 529.5 Hz) 7 gn conforming to EN 60068-2-6 (f = 29.5150 Hz)	
Shock resistance	30 gn conforming to EN 60068-2-27 for 11 ms	
K degree of protection IK02 conforming to EN 50102		

Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	6.0 cm
Package 1 Length	8.6 cm
Package 1 Weight	47.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	32
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.699 kg

Offer Sustainability

REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
RoHS exemption information	ion 🗗 Yes	

Contractual warranty


14.	40 4
Warranty	18 months
vvarianty	10 11011113

Product data sheet Dimensions Drawings

XGHB440845

Dimensions

Updatable Code Electronic Tags




(1) For CHC type screws

XGHB440845


Minimum Mounting Distances

Distance Between Tags



XGCS4901201 smart antenna (format 40)		XGCS8•• smart antennas (format 80)	
e1	e2	e1	e2
30	10	60	10

Minimum Mounting Distances in a Metal Structure





(e) ≥ 20 mm.