



Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle
Type of front plate	Cut-out
Installed device	Source changeover: fixed NS630b...1000 source changeover - control: direct front rotary handle - horizontal installation Source changeover: fixed NS630b...1000 source changeover - control: remote control - horizontal installation Source changeover: fixed NS630b...1000 source changeover - control: automatic - horizontal installation
Poles description	2 x 3P: mounting plate support: NS630b...1000 source changeover horizontal installation 2 x 4P: mounting plate support: NS630b...1000 source changeover horizontal installation
Operating position	Horizontal

Complementary

Enclosure/cubicle description	Cubicle - width 650 mm depth 400 mm
Connection position	Direct connection
Number of vertical modules [50 mm]	13
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA
Material	Steel
Surface finish	Matt Textured
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	650 mm
Width	500 mm
Net weight	3.2 kg
Quantity per set	Set of 1
Functional unit	650 mm 400 mm PrismaSeT P cubicle source changeover NS630b...1000 source changeover fixed direct front rotary handle horizontal 3P 2 direct 13 650 mm 400 mm PrismaSeT P cubicle source changeover NS630b...1000 source changeover fixed direct front rotary handle horizontal 4P 2 direct 13 650 mm 400 mm PrismaSeT P cubicle source changeover NS630b...1000 source changeover fixed remote control horizontal 3P 2 direct 13 650 mm 400 mm PrismaSeT P cubicle source changeover NS630b...1000 source changeover fixed remote control horizontal 4P 2 direct 13 650 mm 400 mm PrismaSeT P cubicle source changeover NS630b...1000 source changeover fixed automatic horizontal 3P 2 direct 13 650 mm 400 mm PrismaSeT P cubicle source changeover NS630b...1000 source changeover fixed automatic horizontal 4P 2 direct 13

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	50 cm
Package 1 Length	65 cm
Package 1 Weight	3.2 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Height	16 cm
Package 2 Width	54 cm
Package 2 Length	67 cm
Package 2 Weight	17.82 kg
Unit Type of Package 3	P12
Number of Units in Package 3	20
Package 3 Height	49 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	71.28 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product