9001SKP7C9

octagonal pilot light Ø 30 - red - incandescent BA 9s - 220/240 V AC- IP66





Main

Range of product	Harmony 9001SK
Product or component type	Pilot light
Device short name	9001SK
Lens type	Domed plastic
Light block supply	Via integral transformer 220240 V AC 50/60 Hz 6 V)

Complementary

Plastic
30 mm
Round
Clear
incandescent
BA 9s
220240 V AC 50/60 Hz
0.8 N.m conforming to EN/IEC 60947-1
Cross slotted
Screw clamp terminals, 1 x 0.222 x 1.5 mm² conforming to EN/IEC 60947-1
10 A
10 A cartridge fuse conforming to EN/IEC 60947-5-1
250 V (pollution degree 2) conforming to EN/IEC 60947-1
2.5 kV conforming to EN/IEC 60947-1
Any position
54 mm
70 mm
42 mm
0.181 kg
Complete product

Environment

Liviloiiiioii	
Electrical shock protection class	Class II conforming to IEC 61140
Protective treatment	TC
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 1
	NEMA 12
	NEMA 13
	NEMA 2
	NEMA 3
	NEMA 3R
	NEMA 4
	NEMA 4X
Vibration resistance	7 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn conforming to IEC 60068-2-27

Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4070 °C	
Standards	JIS C 852	
	EN/IEC 60947-5-1	
	CSA C22.2 No 14	
	UL 508	
	EN/IEC 60947-5-4	
	JIS C8201-5-1	
	EN/IEC 60947-1	
	JIS C8201-1	
Product certifications	UL 508[RETURN]NEMA	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins