# A9A26476

shunt trip release, Acti9, iMX, voltage release, 100...415 V AC





#### Main

9 mm pitches	2	
[Uc] control circuit voltage	100415 V AC 50/60 Hz 110130 V DC	
Device short name	iMX	
Product or component type	Shunt trip release	
Range of product	Acti9	

#### Complementary

Range compatibility	Acti 9 Acti9 iC65	
3	Acti 9 Acti9 ARA	
	Acti 9 Acti9 iDPN Vigi	
	Acti 9 Acti9 iID	
	Acti 9 Acti9 iSW-NA	
	Acti 9 Acti9 RCA	
	Acti 9 Acti9 iDPN (China version)	
	Acti 9 Acti9 iC60 double terminals miniature circuit breaker	
	Acti 9 Acti9 iC40	
Local signalling	Action indicator	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Comb busbar and distribution block compatibility	Top and bottom: YES	
Width	18 mm	
Colour	White	
Connections - terminals	Clamp terminal - 2 cable(s) 2.5 mm <sup>2</sup> - flexible with cable end	
	Clamp terminal - 1 cable(s) 6 mm <sup>2</sup> - rigid	
	Clamp terminal - 2 cable(s) 2.5 mm <sup>2</sup> - rigid	
	Clamp terminal - 1 cable(s) 4 mm <sup>2</sup> - flexible	
Tightening torque	1 N.m	
Compatibility code	IMX	

#### **Environment**

Standards	EN/IEC 60947-5-1	
Tropicalisation	2 conforming to EN/IEC 60947-5-1	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-4085 °C	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.8 cm	
Package 1 Width	3 cm	
Package 1 Length	9.3 cm	
Package 1 Weight	71 g	

Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	8.7 cm
Package 2 Width	10 cm
Package 2 Length	26.7 cm
Package 2 Weight	625 g
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.113 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant <sup>₫</sup> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

#### Contractual warranty

Warranty	18 months