



Main

Range	Merten System Design
Aesthetic name	D-Life
Device presentation	Mechanism with fixing frame and central plate
Outlet standard description	Side earth
Outlet standard deviation	Schuko
Product or component type	Socket-outlet
Socket additional information	Shuttered

Complementary

Outlet poles configuration	2P + E
Wiring device mounting	Flush
Fixing mode	By screws and claws
Colour tint	Anthracite
Connections - terminals	Screwless terminals
Rated current	16 A
[Ue] rated operational voltage	250 V



Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.400 cm
Package 1 Width	14.500 cm
Package 1 Length	21.900 cm
Package 1 Weight	110.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	7.000 cm
Package 2 Width	18.600 cm
Package 2 Length	37.800 cm
Package 2 Weight	632.000 g
Unit Type of Package 3	CAR
Number of Units in Package 3	30
Package 3 Height	35.500 cm
Package 3 Width	37.000 cm
Package 3 Length	40.900 cm
Package 3 Weight	4.320 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations