NSYZZ573G

Polyester glassreinf. plinth for encl. PLAZ(T)73 front opening IP44-IK10 RAL7035





Main

Range	Thalassa
Accessory / separate part categor	Enclosure accessory
Product or component type	Plinth
Application	Multi-purpose
Nominal dimensions of the housing	-
Device composition	Fixing elements 2 front panel 2 side part
Range compatibility	Thalassa Thalassa PLA

Complementary

Fixing mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	500 mm
Width	785 mm
Depth	310 mm

Environment

IP degree of protection	IP44
IK degree of protection	IK10

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	13.0 cm	
Package 1 Width	61.0 cm	
Package 1 Length	80.0 cm	
Package 1 Weight	14.5 kg	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	