RXZE2M114M

socket, Harmony Electromechanical Relays, for RXM2 RXM4 relays, screw connec to rs, mixed contact





Main

| Harmony Electromechanical Relays Harmony Timer Relays |
|--|
| RXZ |
| Socket |
| Plug-in relay RXM with 2 C/O contact[RETURN]Plug-in relay RXM with 4 C/O contact |
| 4 C/O |
| 10 A |
| |

Complementary

| Shape of pin | Flat |
|--|---|
| [Ue] rated operational voltage | < 250 V conforming to IEC < 300 V conforming to UL |
| Contact terminal arrangement | Mixed |
| Connections - terminals | Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end |
| Tightening torque | < 1 N.m for M3 screw(s) |
| Fixing mode | By screw (panel) Clip-on (35 mm symmetrical DIN rail) |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Overvoltage category | III |
| Pollution degree | 3 |
| Sale per indivisible quantity | 10 |
| Width | 27 mm |
| Net weight | 0.056 kg |

Environment

| IP degree of protection | IP20 conforming to IEC 60529 | |
|---------------------------------------|------------------------------|--|
| Dielectric strength | 3000 V | |
| Standards | IEC 61984 | |
| Product certifications | UL[RETURN]CSA[RETURN]Lloyd's | |
| Marking | CE | |
| Ambient air temperature for storage | -4085 °C | |
| Ambient air temperature for operation | -4055 °C | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 2.686 cm | |
| Package 1 Width | 4.245 cm | |
| Package 1 Length | 7.918 cm | |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| Package 1 Weight | 0.054 kg |
|------------------------------|----------|
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 7.5 cm |
| Package 2 Width | 8.8 cm |
| Package 2 Length | 14.0 cm |
| Package 2 Weight | 0.561 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 230 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 12.42 kg |

Offer Sustainability


| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh Regulation | ☑ REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | ☑ China RoHS Declaration |
| RoHS exemption information | ₫Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Contractual warranty

| <u></u> _ | |
|-----------|-----------|
| Warranty | 18 months |

RXZE2M114M

Dimensions



- (1) Relays
- (2) Protection module
- (3) Maintaining clamp
- (4) 2 elongated holes Ø 3.5 mm x 6.5 mm / Ø 0.13 in. x 0.25 in.

Wiring Diagram

