

Product data sheet Characteristics

XACA9413

round head for pushbutton - spring return - XAC-A - green - booted



Main

Mairi		
Range of product	Harmony XAC	
Product or component type	Head for push-button	
Component name	XACA	

Complementary

Marking	Unmarked
Operator additional information	Booted
Cap/operator or lens colour	Green
Product compatibility	XACA
Mounting location	Front of enclosure
Sale per indivisible quantity	10
Standards	IEC 60947-5-1 CSA C22.2 No 14 UL 508 IEC 60204-32
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Vibration resistance	15 gn (f= 10500 Hz) conforming to IEC 60068-2-6
Shock resistance	100 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Net weight	0.01 kg

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.0 cm	
Package 1 Width	14.0 cm	
Package 1 Length	17.0 cm	
Package 1 Weight	9.0 g	
Unit Type of Package 2	BAG	
Number of Units in Package 2	10	
Package 2 Height	3.0 cm	
Package 2 Width	7.5 cm	
Package 2 Length	11.0 cm	
Package 2 Weight	94.0 g	
Unit Type of Package 3	S03	

Number of Units in Package 3	700
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	7.068 kg

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

Warranty 18 months	
--------------------	--