

Main

| | |
|---------------------------|-------------------|
| Range of product | 9007 |
| Series name | Heavy duty |
| Product or component type | Snap limit switch |
| Device short name | 9007AO/CO |
| Body type | Fixed |

Complementary

| | |
|--|---|
| Mounting mode | - |
| Operator profile | Plunger head |
| Material | Metal |
| Body material | Cast zinc |
| Operator material | Cast zinc |
| Fixing mode | By the body |
| Movement of operating head | Linear |
| Type of operator | Spring return roller lever plunger metal no bracket + 0.22" roller |
| Switch actuation | By 30° cam |
| Type of approach | Traverse approach, 2 directions |
| Electrical connection | 1...2 cables for 6 binder head screw terminals (AWG 22...AWG 14) |
| Number of poles | 2 |
| Contacts type and composition | 2(NC-NO), switch function: DPDT-DB |
| Contact form | Form ZZ |
| Contact operation | Snap action |
| Number of steps | 1 |
| Contacts material | Silver contacts |
| Positive opening | Without |
| Terminals description ISO n°1 | (1-2)NC (7-8)NO (3-4)NO (5-6)NC |
| Minimum force for tripping | 0.5 lbf |
| Maximum force for tripping | 0.5 lbf |
| [Ie] rated operational current | 0.6 A at 600 V AC, B600 conforming to NEMA rating designation 0.75 A at 480 V AC, B600 conforming to NEMA rating designation 1.5 A at 240 V AC, B600 conforming to NEMA rating designation 3 A at 120 V AC, B600 conforming to NEMA rating designation 0.1 A at 250 V DC 0.2 A at 125 V DC |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 600 V (pollution degree 3) conforming to UL 508 for contact block 600 V conforming to CSA C22.2 No 14 for contact block |
| Width | 24.13 mm |
| Height | 63.50 mm |
| Depth | 64.52 mm |
| Net weight | 0.68 kg |


Environment

| | |
|---------------------------------------|------------------------------------|
| NEMA degree of protection | NEMA 1 conforming to Nema type 250 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Ambient air temperature for operation | -29...85 °C |
| Ambient air temperature for storage | -29...85 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.452 cm |
| Package 1 Width | 2.54 cm |
| Package 1 Length | 16.387 cm |
| Package 1 Weight | 680.389 g |

Offer Sustainability

| | |
|--|---|
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|