

9007CR61E

Limit switch, 9007, 9007CR 2 NO/NC, top push rod plunger



Main

| | |
|-------------------------------|---|
| Range of product | 9007 |
| Series name | Heavy duty |
| Product or component type | Limit switch |
| Product specific application | Hazardous location box |
| Device short name | 9007CR |
| Body type | Fixed |
| Head type | Plunger head |
| Material | Metal |
| Fixing mode | By the body |
| Movement of operating head | Linear |
| Type of operator | Stainless steel spring return plunger (-) |
| Switch actuation | On end |
| Type of approach | Vertical approach, 1 direction |
| Electrical connection | Screw-clamp terminals (AWG 22...AWG 12), 1...2 |
| Cable entry | 1 entry for 1/2" - 14 NPT conforming to ANSI B1.20.1 |
| Number of poles | 2 |
| Contacts type and composition | 2(NC-NO) |
| Contact operation | Snap action |
| Positive opening | Without |
| Level or class | Class II Division 1 Groups E/F/G Class I Division 1 Groups B/C/D |
| Sale per indivisible quantity | 1 |

Complementary

| | |
|--|--|
| Body material | Aluminium |
| Head material | Zinc |
| Function available | - |
| Switch function | DPDT-DB |
| Contact form | Form ZZ |
| Contacts material | Silver contacts |
| Terminals description ISO n°1 | (5-6)NC (1-2)NC (3-4)NO (7-8)NO |
| Minimum force for tripping | 3 lbf |
| Repeat accuracy | +/- 0.001 in linear travel of cam |
| [Ie] rated operational current | 1.2 A at 600 V AC, A600 conforming to NEMA 1.5 A at 480 V AC, A600 conforming to NEMA 3 A at 240 V AC, A600 conforming to NEMA 6 A at 120 V AC, A600 conforming to NEMA 0.11 A at 250 V DC, R300 conforming to NEMA 0.55 A at 125 V DC, R300 conforming to NEMA |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 600 V (pollution degree 3) conforming to UL 508 for contact block 600 V (pollution degree 3) conforming to CSA C22.2 No 14 for contact block |

| | |
|--|--|
| [Uimp] rated impulse withstand voltage | 2.5 KV AC 1 min conforming to CE 2.2 KV AC 1 min conforming to UL 2.64 kV AC 1 s conforming to CSA |
| Short-circuit protection | 10 A by CC fuse, protection type: non-time delay |
| Electrical durability | 1000000 cycles |
| Local signalling | without |
| Mechanical durability | 10000000 cycles |
| Width | 69.09 mm |
| Height | 167.13 mm |
| Depth | 52.83 mm |
| Net weight | 1.13 kg |


Environment

| | |
|---------------------------------------|---|
| Shock resistance | 60 gn for 9 ms conforming to IEC 60068-2-27 |
| Vibration resistance | 25 gn (f= 10...150 Hz) conforming to IEC 60068-2-6 |
| NEMA degree of protection | NEMA 1 conforming to Nema type 250 NEMA 2 conforming to Nema type 250 NEMA 4 conforming to Nema type 250 NEMA 6 conforming to Nema type 250 NEMA 6P conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| Electrical shock protection class | Class 0 conforming to IEC 61140 |
| Ambient air temperature for operation | -29...85 °C for hazardous location |
| Ambient air temperature for storage | -29...85 °C |
| Environmental characteristic | Standard environment |
| Protective treatment | Epoxy powder coat |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.452 cm |
| Package 1 Width | 2.54 cm |
| Package 1 Length | 16.387 cm |
| Package 1 Weight | 1.134 kg |

Offer Sustainability

| | |
|--|--|
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|