# XGHB320345

Electronic tag, Radio frequency identification XG, RFID 13.56 MHz, disc Ã~ 30 x 3, 112 Bytes



#### Main

Range of product	Telemecanique Radio frequency identification XG		
Product or component type	Electronic tag		
RFID electronic tag name	XGHB		
RFID frequency	13.56 MHz		
Design	Disc		
Memory capacity	112 B		
Associated smart antenna	XGCS		
[Sn] nominal sensing distance	42 Mm with XGCS49 + field expander XGFEC540 48 Mm with XGCS49 65 Mm with XGCS89 80 Mm with XGCS49 + field expander XGFEC2525 65 mm with XGCS85		
Outer dimension	Ø 30 x 3 mm		
Quantity per set	Set of 5		
Read time	12 + 0.825 x (number of 16-bit words) ms		
Write time	12 + 5.6 x (number of 16-bit words) ms		
IP degree of protection	IP68		
Fixing mode	By screws		

#### Complementary

Complementary		
Memory type	EEPROM	
Memory operation	Read/write	
Number of read cycles	Unlimited	
Number of write cycles	2500000 at 30 °C 100000 at -2585 °C	
Maximum linear speed with "auto read/write function"	3.1 M/S with XGCS49 (read a serial number) 1.4 M/S with XGCS49 (read a word) 0.7 M/S with XGCS49 (read or write 10 words) 5.8 M/S with XGCS89 (read a serial number) 2.7 M/S with XGCS89 (read a word) 0.9 M/S with XGCS89 (read or write 10 words) 5.8 M/S with XGCS85 (read a serial number) 2.7 M/S with XGCS85 (read a word) 0.9 m/s with XGCS85 (read or write 10 words)	
Data retention time	10 year(s)	
Material	PPA (polyphthalamide)	
Net weight	0.005 kg	
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	

## **Environment**

Standards	ISO 15693	
Ambient air temperature for operation	-2585 °C	
Ambient air temperature for storage	-4090 °C	
Vibration resistance	2 mm conforming to IEC 60068-2-6 (f = 529.5 Hz) 7 gn conforming to IEC 60068-2-6 (f = 29.5150 Hz)	
Shock resistance	30 gn conforming to IEC 60068-2-27 for 11 ms	
IK degree of protection	IK02 conforming to IEC 62262	

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.400 cm
Package 1 Width	3.000 cm
Package 1 Length	3.000 cm
Package 1 Weight	3.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	6.000 cm
Package 2 Width	9.000 cm
Package 2 Length	10.000 cm
Package 2 Weight	19.000 g
Unit Type of Package 3	S01
Number of Units in Package 3	250
Package 3 Height	15 cm
Package 3 Width	15 cm
Package 3 Length	40 cm
Package 3 Weight	1.080 kg

# Offer Sustainability

Sustainable offer status	Green Premium product	
Toxic heavy metal free Yes		
California proposition 65  WARNING: This product can expose you to chemicals in phthalate (DINP), which is known to the State of Californian and Di-isodecyl phthalate (DIDP), which is known to the to cause birth defects or other reproductive harm. For more www.P65Warnings.ca.gov		
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com	

# Contractual warranty

	Warranty	18 months
--	----------	-----------



# Product data sheet Dimensions Drawings

# XGHB320345

## **Dimensions**

# Updatable Code Electronic Tags





# XGHB320345

## Minimum Mounting Distances


## **Distance Between Tags**



XGCS4901201 smart antenna (format 40)		XGCS8•• smart antennas (format 80)	
e1	e2	e1	e2
70	50	190	60

# Minimum Mounting Distances in a Metal Structure


No metal parts within 15 mm of the tag




- (e) ≥ 15 mm.
- (1) Tightening torque ≤ 1 Nm/0.74 lb-ft
- (2) Insulation material

#### Curves

# Dialogue Zones for Field Expanders






(1) Recommended working zone.

#### Curves

# Dialogue Zones for Field Expanders



(1) Recommended working zone.