Product data sheet
Characteristics

XUSZSM3B
Telemecanique Safety light curtains XUSL, Column for 3 beams light curtain integrated muting

Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part category	Mounting and fixing accessories
Accessory / separate part type	Fixing column
Offer type	Without mirror
Product compatibility	XUSL4M.3B....
Accessory / separate part destination	Safety light curtain type 4 with integrated muting function

Complementary

Ambient air temperature for operation	-30…55 °C -30…55 °C
Ambient air temperature for storage	-30…70 °C -30…70 °C
Column height	1200 mm
Height protected	810 mm
Net weight	3.7 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	19.5 cm
Package 1 Length	130.0 cm
Package 1 Weight	3.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Telemecanique
Sensors