Product data sheet Characteristics

ZCMD41L5

Limit switch body, Limit switches XC Standard, ZCMD, 2NC+2 NO, silver, snap action, connection, 5 m



Main

| Range of product | Telemecanique Limit switches XC Standard |
|-------------------------------|--|
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCMD |
| Design | Miniature |
| Body type | Fixed |
| Associated head | ZCE67 ZCE09 ZCE62 ZCE10 ZCE64 ZCE11 ZCE65 ZCEG1 ZCE06 ZCE13 ZCE08 ZCE7 ZCE24 ZCE07 ZCE24 ZCE07 ZCE21 ZCE66 ZCE14 ZCE28 ZCEF2 ZCE27 ZCE02 ZCE29 ZCE01 ZCE06 |
| Body material | Zamak |
| Number of poles | 4 |
| Contacts type and composition | 2 NC + 2 NO |
| Contact operation | Snap action |

Complementary

| Complementary | |
|--|---|
| Product compatibility | XCMD |
| Electrical connection | Fixed cable |
| Cable length | 5 m |
| Cable composition | 9 x 0.34 mm² |
| Wire insulation material | PvR |
| Contacts insulation form | Zb |
| Contacts material | Silver plated contacts |
| Positive opening | With |
| Minimum actuation speed | 0.01 m/min |
| [Ui] rated insulation voltage | 300 V (pollution degree 3) conforming to UL 508 400 V (pollution degree 3) conforming to IEC 60947-5-1 300 V (pollution degree 3) conforming to CSA C22.2 No 14 |
| Maximum resistance across terminals | 25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 4 KV conforming to IEC 60664 4 kV conforming to IEC 60947-1 |
| Short-circuit protection | 6 A cartridge fuse, type gG |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intermed as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation in the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| Electrical durability | 5000000 Cycles, DC-13 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 48 V, 2 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 120 V, 1 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
|-------------------------------------|--|
| Width | 30 mm |
| Height | 50 mm |
| Depth | 16 mm |
| Net weight | 0.065 kg |
| Environment | |
| Ambient air temperature for storage | -4070 °C |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.0 cm |
| Package 1 Width | 18.5 cm |
| Package 1 Length | 20.0 cm |
| Package 1 Weight | 462.0 g |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 160 |
| Package 2 Height | 60.0 cm |
| Package 2 Width | 80.0 cm |
| Package 2 Length | 160.0 cm |
| Package 2 Weight | 76.0 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 20 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 9.943 kg |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. |

| Sustainable offer status | Green Premium product |
|--|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| Warranty 18 | months |
|-------------|--------|
|-------------|--------|

